

# Technical data sheet for SINGLE PAN ELECTRIC FRYER 450mm

E43E

- 17kW high performance single pan fryer
- Digital display temperature control with 3 product timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 27L oil capacity
- 32mm (1 <sup>1</sup>/<sub>4</sub>") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



#### **Overall Construction**

- Stainless steel pan
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Hinge out counterbalanced heating elements
- 32mm (1 <sup>1</sup>/<sub>4</sub>") drain valve
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

#### Controls

- Digital display electronic thermostat
- Thermostat range 88-193°C
- 3 programmable product timers with countdown display and alarms
- Straight or compensating temperature cook time control
- Heating and basket drop displays
- Programmable melt cycles
- Fail-safe over-temperature safety cut-out
- Element tilt switch for heating cut-out on element lift

#### **Cleaning and Servicing**

- Open stainless steel pan with hinge out elements for easy clean
- Easy clean basket support bar
- $\bullet$  32mm (1  $^{1}/\!\!\!4$  ") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all controls from front of unit

## Technical data sheet for SINGLE PAN ELECTRIC FRYER 450mm

#### Specifications Production rate 31kg/hr

Pan Size Oil capacity 27L (50lbs shortening) Width 365mm Length 380mm Oil frying depth 95mm

#### Baskets

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H

#### Elements

3 x 5.66kW stainless steel heating elements

# Electrical requirements 17kW, 400-415Vac, 50/60hz, 3P+N+E L1 23.6A L2 23.6A L3 23.6A

#### Dimensions

Width 450mm Depth 812mm Height 915mm Incl. splashback 1085mm

### Nett weight


64kg

#### Packing data 0.54m3, 105kg

Width 870mm Depth 495mm Height 1255mm

#### Options

Adjustable feet at rear Filtamax Filtration System Extra baskets Side splash guards Joining caps Castors





#### MOFERT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

www.bluesealevolution.com

Australia Moffat Pty Limited

#### Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

#### New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

**Queensland** Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6802 bgarcia@moffat.com.au

#### New Zealand Moffat Limited

Christchurch 16 Osborne Street Christchurch 8011 Telephone 03-389 1007 Facsimile 03-389 1276 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz



ISO9001 Quality Management Standard

ned and manufactured by

## MOFFAT.

ISO9001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in China © Copyright Moffat Ltd Moffat/4825/BH/2.5M/12.06



